

WSS-716

Product technical specification

WSS-716 is for the wetting an aqueous formulation base, also for solvent-wetting formulation. Good recoatability is especially suitable for automotive paint wetting agent, industrial coating wetting agent, plastic coating wetting agent, architectural coating substrate wetting agent, inkjet ink wetting agent , based on polyurethane, acrylic resin nitro and cheese Leather pre-coated primer of plain emulsion system.

- Suitable for water-based and solvent-based formulations
- High performance
- Good recoatability

Recommended Applications

- Automotive paint , industrial paint , plastic , wood and furniture paint
Recommended amount
Based on the supply form to the total formula: 0.1-1.0%
- Architectural Coatings
Recommended amount
As supplied calculated on total formulation: 0 .1 1.0 %
- Decorative paint , inkjet ink
Recommended amount
Calculated in the form of supply, 0.2-1.0% of the total formula
- Leather pre-coating primer , primer and topcoat based on polyurethane , acrylic resin , nitro and casein systems
Recommended amount
Calculated in the form of supply, 0.2-1.0% of the total formula

Technical data

- Appearance : transparent liquid
- Active matter content : 100%

chemical composition

Organosiloxane copolymer

Process Description

Pre-diluted or directly added to the paint in the form of supply

package

- 25 kg , plastic drum ○ 200 kg , iron drum

Storage stability

Store in unopened original packaging and use within 12 months from the date of production .

Free samples or detail:

Please contact: 006598831607 (Singapore) Mr. Yang